



# Your One-Stop Solution for Tools, Safety & Outdoor Essentials

## FIRE RETARDANT TARPAULINS 300 GSM

### OVERVIEW



HP Tarpaulins can be stitched and Welded by High Frequency welding machine with special Grommets / Eyelets, Reinforcements and Webbing as per customer's requirements maximum size upto 60FT x 60FT (18MTR x 18MTR).

Parameter	Specification
Product Code	2209
Finished Coated Weight	300 gsm/SQM
Base Fabric	Polyester 200Dx500D, 18x12/inch
Tensile Strength	L 1600N/5cm, W 1475N/5cm (ASTM D5035)
Tear Resistance	L 300N/5cm, W 279N/5cm (ASTM D1004)
Adhesion	L ≥ 80N, W ≤ 80N (ASTM D5035)
Thickness	0.35 mm
Width	72 Inch (180 cm)
Fire Retardancy	Passed (BS5867)
Temperature Resistance	-20 ~ 70 °C
Package	72" x 50 yds
Characteristics	Excellent Waterproof, UV Treated, Anti Cold Crack, Oil Resistance, Fire Retardant
Applications	Tents, Tarpaulins, Oil & Gas Stores, Equipment Covers, Boat Covers

#### Ready Made Sizes

18 FT x 24 FT (5.5m x 7.2m) 30 FT x 30 FT (9m x 9m) 60 FT x 60 FT (18m x 18m)  
 20 FT x 20 FT (6m x 6m) 40 FT x 40 FT (12m x 12m)

### THE BENEFITS



#### Characteristics:

Excellent water proof | U.V. treated. | Anti cold crack. | Oil resistance. | Fire retardant.



#### Applications:

Oil & gas stores | Tarpaulins  
 Equipment covers | Tents | Boat Covers



#### Standard Colours:

Green,Blue,White,Gray,Orange